

ETC330-GB LED

Inground luminaires

1/10

we-ef



Broad Museum L.A., USA

WE-EF LIGHTING Co Ltd


57 Moo 5 | Kingkaew Rd | Bangplee | Samutprakarn 10540 | Thailand | Tel +66 2 738 9610 | Fax +66 2 175 2174 | info.thailand@we-ef.com | www.we-ef.com | 27-07-2022 06:33
Technical modifications and errors excepted

ETC330-GB LED

Inground luminaires

2/10

we-ef



Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 0.5 m of flexible PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request. Luminaire installation blockout and sealable junction box included in supply.

ETC330-GB LED


Inground luminaires

3/10

we-ef

Specifications

Material Specification

Body:	Stainless steel construction
Lens:	Safety glass lens, max. load 5 tonnes
Colours:	 Stainless Steel
Gasket:	Silicone rubber gasket
Fasteners:	PCS hardware
Ingress protection:	IP67
Impact protection:	IK10+
Mounting:	Luminaire installation blackout and sealable junction box included in supply

Electrical Specification

Driver / Ballast:	Integral EC electronic converter
Cable:	Complete with cable gland and 0.5 m of flexible PVC-free cable

ETC330-GB LED









Inground luminaires

4/10



Choices

Light Distributions

	Nominal Lumen	Nominal Watt	Colour Temperatures	Colours
 symmetric, wide beam [B]	1398 1476	12 18	 2700 K	 Stainless Steel
 symmetric, medium beam [M]	2220 2340		 3000 K	
 symmetric, very narrow beam [EE]	2700		 4000 K	
 symmetric, very narrow beam, 'sharp cut-off' [EES]				





ETC330-GB LED

Inground luminaires




5/10



Configurations

Light Distributions	Part ID	Light Source	Rated Lumens	Rated Input Power	CRI	Weight	Link
 symmetric, wide beam [B]	185-7831	LED-6/12W / 700 mA - 2700 K	1056.9	14	80	8.00	📄 ↗
	185-9672	LED-6/12W / 700 mA - 3000 K	1156.6	15	80	8.00	📄 ↗
	185-9676	LED-6/12W / 700 mA - 4000 K	1156.6	15	80	8.00	📄 ↗
	185-7834	LED-6/18W / 1050 mA - 2700 K	1632.8	21	80	8.00	📄 ↗
	185-7762	LED-6/18W / 1050 mA - 3000 K	1721	21	80	8.00	📄 ↗
	185-7766	LED-6/18W / 1050 mA - 4000 K	1985.8	21	80	8.00	📄 ↗
 symmetric, medium beam [M]	185-7828	LED-6/12W / 700 mA - 2700 K	1230.7	14	80	8.00	📄 ↗
	185-7233	LED-6/12W / 700 mA - 3000 K	1299.4	15	80	8.00	📄 ↗
	185-7236	LED-6/12W / 700 mA - 4000 K	1299.4	15	80	8.00	📄 ↗
	185-7832	LED-6/18W / 1050 mA - 2700 K	1860.9	21	80	8.00	📄 ↗
	185-7760	LED-6/18W / 1050 mA - 3000 K	1961.4	21	80	8.00	📄 ↗
	185-7764	LED-6/18W / 1050 mA - 4000 K	2263.2	21	80	8.00	📄 ↗
 symmetric, very narrow beam [EE]	185-7829	LED-6/12W / 700 mA - 2700 K	1202.8	14	80	8.00	📄 ↗
	185-7232	LED-6/12W / 700 mA - 3000 K	1269.9	15	80	8.00	📄 ↗
	185-7235	LED-6/12W / 700 mA - 4000 K	1269.9	15	80	8.00	📄 ↗
	185-7833	LED-6/18W / 1050 mA - 2700 K	1761	21	80	8.00	📄 ↗
	185-7761	LED-6/18W / 1050 mA - 3000 K	1856.2	21	80	8.00	📄 ↗
	185-7765	LED-6/18W / 1050 mA - 4000 K	2141.8	21	80	8.00	📄 ↗
 symmetric, very narrow beam, 'sharp cut-off' [EES]	185-7830	LED-6/12W / 700 mA - 2700 K	1305.4	14	80	8.00	📄 ↗
	185-7227	LED-6/12W / 700 mA - 3000 K	1378.2	15	80	8.00	📄 ↗
	185-7229	LED-6/12W / 700 mA - 4000 K	1378.2	15	80	8.00	📄 ↗

Related Families / ETC300-GB

Family		Dimensions	Wattage	Nominal Lumen	Links	
					Links	Download Data Sheet
ETC320-GB LED		160	6 -9 W	699 -1350	📄 ↗	📄 ↓
ETC330-GB LED		250	12 -18 W	1398 -2700	📄 ↗	📄 ↓
ETC340-GB LED		300	24 -36 W	2796 -5400	📄 ↗	📄 ↓

ETC330-GB LED

Inground luminaires

6/10

we-ef

Mounting Accessories

Installation cover


■ **185-0325** Installation cover BE



Optical Accessories

Colour filter

■ **on request** Colour filter IF



Flood lens

ETC330-GB LED

Inground luminaires

7/10

we-ef

■ **185-9679** Flood lens IO-360



C1

ETC330-GB LED


Inground luminaires

8/10

we-ef

Honeycomb louvre

■ **185-0143** Honeycomb Louvre IW



C1

Linear louvre

■ **185-9677** Linear louvre IL



C1

ETC330-GB LED


Inground luminaires

9/10

we-ef


Linear spread lens

■ **185-9678** Linear spread lens IO-180



Optical Adaptor

■ **185-7420** Internal optical Adaptor IA



ETC330-GB LED

Inground luminaires

10/10

we-ef

Control

1-10 V analogue dimming interface

■ **430-0011** 1-10 V analogue dimming interface

DALI interface

■ **430-0013** DALI interface